

# EMERGENCY LED LIGHT



## WALL MOUNT

Emergency lighting is a vital and effective life safety tool, providing reassurance and guidance to people at critical times when they need to escape quickly and safely from a building.

## EMERGENCY LIGHTING SYSTEM FEATURES

Exlite series emergency LED exit signages get switched on upon failure of main power supply and provides illumination through the battery source for a standard duration of 2 hours. It automatically gets recharged upon resumption of main power supply.



Model No: EXL-LED-W

Aesthetically designed with care and elegance



Uniformly illuminated without hot spots, giving the luminaire a flawless finish.



Highest quality and standards.



Clear frame and low profile ensures seamless integration into the surrounding architecture.



Exit Light is a luminaire, that indicates and assists the identification of escape routes.

## CEILING MOUNT



Model No: EXL-LED-C

## Technical Specifications

| TYPE               | Wall mount   | Ceiling Mount  |
|--------------------|--|--|
| Model No           | <b>EXL - LED - W</b>   | <b>EXL - LED - C</b>   |
| Body               | C.R.C.A Sheet Steel – 22 S.W.G                                       | Made up of uniformly extruded aluminium alloy.                             |
| Message Panel      | CAD Designed & Cut vinyl on 2 M. M. thick milky White acrylic panel. | CAD Designed printing /itching / engraving on 10 M. M. clear acrylic sheet |
| Dimensions         | 360 mm (W) * 180 mm (H)  | 300 mm (W) * 180 mm (H)  |
| Ingress Protection | IP – 20  |  |
| Paint & Colour     | Epoxy polyester powder coating, White in colour.                     | Epoxy polyester powder coating/ white in color                             |
| Input              | ~ 230 Volts, 50 Hz.  |  |
| Mains Connector    | 5A, 250 Volts, Polycarbonate with electrical grade brass contacts    | 5A, 250 Volts, PCB Mount with electrical grade brass contacts.             |
| Mounting           | On wall through 2 Nos. of Holes                                      | Ceiling with 2 Nos. of hooks   |
| Confirms to        | IS: 9583 – 1981.   |  |
| Weight             | ~ 2 kg   | ~ 1 kg   |
| Tube Type          | Multiple LED's   |  |
| Lamp               | 5W   |  |
| LED Make           | Seoul/Osram/Lumiled/Ever Light                                       |  |
| Type               | Rechargeable; Ni-Cd / Ni-Mh  |  |
| Duration           | 120 minutes backup; + 10%  |  |
| Recharging Cycle   | 16 – 24 hours recharging period                                      |  |