

POWER SUPPLY 24V/5A WITH BATTERY BACKUP - SMPS

Model No: BPS-SA-240507

Unique Features:

- Maximum output power of 120W.
- High efficiency, High reliability, Low cost.
- AC input voltage range 170 270V AC
- Built-in input over voltage protection.
- Low Ripple and Noise.
- Compact, Light weight.
- Momentary output short circuit protection.
- 100% Full load burn-in test.
- Built in battery charging provision.
- . Low battery cut off provision, to prevent the battery drain condition.
- Constant current charging for Battery.

Specifications:

All these parameters are specified at 230V AC input.

Input Characteristics

| Input Voltage | 170-270 VAC |
|------------------|--------------------|
| Input Frequency | 47 - 63 Hz |
| Efficiency | 88% |
| AC Current | 0.7Amp (230 VAC) |
| Inrush Current | 35 Amp (230 VAC) |
| Leakeage Current | Less than 3.5mA |
| Input Connector | 3-pin plug |

Input Protections

Protected upto 320VAC

SMPS Shutsdown if I/P less than 80VAC,

Resumes operation when I/P is

Between 80VAC - 270VAC

Between 80 VAC - 170 VAC

unit gives O/P in 50 % Power

Thermal Overload: Protected, Auto Recovery.

1.5Amp, 20mm fast blow, Glass fuses.

MOV for input over voltage protection.

Environmental Characteristics

| Operating | -20 to 50DEG C |
|-------------------|--------------------------|
| Temperature | 70 C at 60% Load |
| Cooling | Forced cooling |
| Relative Humidity | 20- 90 RH Non Condensing |

General Characteristics

| Dimension (L X H X D) mm | (310 X 310 X 98) |
|--------------------------|--------------------|
| Mounting | Wall Mounting |

Output Characteristics

| Output Voltage | 24 - 26VDC |
|----------------|------------|
| Output Current | 5 A |
| Output Power | 120 W |

LED Indications

| Ac power | Yellow |
|-------------|--------|
| Output | Green |
| Battery | Blue |
| Low Battery | Red |

Output Connector & Battery Connector

2-pin screw type connector.

Protection

| Low Battery cut off | 20.00V |
|-------------------------------------|--------|
| Output Over Voltage Protected 29VDC | |

Regulation

| Line Regulation | 0.5% (FULL LOAD) |
|------------------|--------------------|
| Load Regulation | 1% (230VAC I/P) |
| Ripple and Noise | 1 % P-P. |

Isolation

| I/P - O/P | 3000V AC |
|-------------|-------------------------------|
| I/P - Earth | 2000V AC |
| O/P - Earth | 1000V AC |
| | 5.010000 00000 0000000 000000 |

Recommended Battery

| Battery | Sealed Lead Acid Battery |
|--------------|--------------------------|
| Quantity | 2 Nos in Serious |
| Battery link | provide, Fuse Protected |

^{*} For continuous improvement, specifications are subject to change.

⁰